



HomeEye Introduction

2019/01/01



- 1080P Battery IP Cam
- 360° Panoramic IP Cam
- 4G SolarPower Bullet Cam
- Wi-Fi SolarPower Cam
- NVR + 4 Wifi-Cam
- Detachable Solar Power IP CAM



HomeEye Series



HD Battery IP Cam
HE01



Panorama IP Cam
PI2E




4G Solar Bullet Cam
SP-4G



Wi-Fi Solar Bullet Cam
SP-WF



NVR + 4Cam
NVR-4C



Detachable Solar Cam
DSP

Battery IPCam



- 100% Wire-Free
- HD Quality
- All-day service
- Night Vision
- Motion detection alarm
- Cloud Storage

Weatherproof Design

Place the camera outdoors/indoors without worrying about the weather.
It guards you no matter rain or shine.



1080P Battery IP Cam



Simple Setup & Operation



Superior Night Vision



Motion-Activated HD Video Alerts



Stylish and Durable Design for
Indoor and Outdoor Applications



24/7 Monitoring



Siren Alert



Vibrant FHD Video Quality



Local and Cloud Storage Options



Two-Way Audio

Hardware Features

1/2.7" 1080P CMOS image sensor
2.90mm@F2.4 EFL 133°Field of View
Auto night vision mode
H.264 video compression engine
FHD video resolution
Motion detection using smart PIR sensor
Siren alert
Micro SD slot supporting cards up to 128GB
Two-Way audio
802.11 b/g/n Wi-Fi
Lithium Ion battery supporting up to six months of standby time
DC 5V Micro-USB power connector
Operating Temperature range of -10°C ~ 50°C
Humidity < 95% (non-condensing)
51mm x 80mm x 73mm (W x D x H)
Weight: 165g
Camera mount
FCC / CE / CPSC / REACH / ROHS/ WEEE / BSMI / NCC



Power Consumption

1. In normal setting, the camera can record ten 5-second clips.
The battery life is 140 days
2. If it records forty 30-second clips a day, the battery life is 28 days.
3. In standby mode, the battery life is 182 days (around 6 months)
The camera has an IR illumination range of up to 5 meters
(depending on the environment)

Night Vision 24 hours for your guardian



Turn on infrared light at night,
always watch the situation in the dark.



Remote call anytime and anywhere

Two-Way Audio

Vpai Home panoramic camera supports two-way audio, one-way video call function, one key starts talking, talk to your family anytime and anywhere.

360° Panoramic IP Cam



Simple Setup & Operation



Vibrant 2K Video Quality



Superior Night Vision



24/7 Monitoring



Local and Cloud Storage Options



Motion-Activated FHD Video Alerts

360°Panoramic IP Cam

360°panoramic monitor with all angles

VPai Home Panoramic IP Cam can let you monitor your rooms every corners.



Dual-fisheye
Sensors



APP Support



Live Preview



Share Camera



VR experience



Wi-Fi

Hardware Features

- Dual 210° fisheye lenses with transverse 360° and longitudinal 360° capture
- 2048×1024 (2K) video and image resolution
- 2 x 1.07mm@F2.0 EFL 210° Field of View
- Auto night vision mode
- H.264 video compression engine
- Micro SD slot supporting cards up to 128GB



- 802.11 b/g/n Wi-Fi
- DC 5V Micro USB power connector
- Operating temperature range of -10°C ~ 50°C
- Humidity < 95% (non-condensing)
- 40mm x 30mm x 88.5mm (W x D x H)
- Weight: 88g
- Camera accessories: pedestal

360° Panoramic IP Cam Spec

Product Spec	Camera	Sensor	1/2.7" 1080P CMOS *2
		Lens	3.04mm@ F2.0, Field Angle:210° *2
		Day/Night Mode	ICR Infrared filter
	Video/Audio	Video Codec	H.264 Main Profile
		Video bitrate	High/Normal/Low, Auto Adapter
		Audio Codec	AAC
		Audio Bitrate	Auto adaptive
	Image	Max. Image Resolution	2048*1024
		FPS	<= 20FPS, Auto Adaptive
		Backlight	Support
	Function	Storage	Micro SD (Max. 128G)
		Alarm	Motion Detection
		Wi-Fi	IEEE802.11b/g/n 2.4G
	Operating Condition	Temperature/Humidity	-10℃~50℃, Humidity < 95% (No condensation of moisture)
		Power Supply	DC 5V (Micro USB)
		Power Consumption	2.2W
		IR illuminates range	MAX 10 meters (Depends on environment)
		Dimension(mm)	42MM*50MM*83.4MM
		Weight	TBD(Net.)
	APP	Android, iOS	

360° Panoramic IP Cam

360° Panoramic Camera

Dual fisheyes sensors provide immersive full-angle experiences, no more blind spot.




360° Panoramic IP Cam

360° Panoramic Camera

Dual fisheye lenses provide full-room view without blind spots overcoming the limitations of traditional home security cameras.

You can see wherever you want !



1, 2 or 4 Views

360°Panoramic IP Cam

Motion Detection Guards Against Any Threat to Home Security

360°Panoramic IP Cam Guard automatically records a ten-second clip when it detects an intruder and sends an alarm to your smart phone.



10:11

Motion Detection

VPai Home 1




09:50

Motion Detection

VPai Home 1





- Server Relay
- Proprietary P2P technology
- Unlimited Bandwidth
- Stable and Reliable Connection
- Instant Playback



Alarm-triggered events are stored to the cloud automatically




Worldwide Relay Service

China/Singapore/Japan/Hongkong/USA/...

Seamless Home Network Connectivity

Easy wireless access via the router from anywhere.



Playback the cloud video with any time

24 hours of history record playback, no images you care about will miss, the minute level accurate positioning, browse, download and share.



The camera supports multiple members sharing

Multiple people can watch it at the same time,
guardian together.



Easy to use with APP

With Wi-Fi connection, no need complex wire.
3 steps to connect the device



Download APP



Turn on device



Pair and Play

4G Solar Bullet Cam: SP-4G

Wireless Device, Plug 4G Card & Play

Solar power camera with a 4G module.
Automatically connect to the Internet by insert
Sim card or data card.
Convenient and quick with no cable connection.





4G Solar Bullet Cam: SP-4G

Hardware Features

- 1/2.7" 1080P CMOS image sensor (PS5230)
- HD lens F2.8 FOV
- 90° Field of View
- Auto night vision mode
- H.264 video compression
- Siren aler
- Motion detection using smart PIR sensor
- Two-Way audio, Support Full duplex intercom
- 850nm IR ray, 9m distance
- FHD resolution: 1920*1080/15fps, 640*360/30fps
- Micro SD slot supporting cards up to 64GB
- 2*18650 Li-battery, up to 60 days of standby time
- DC 5V Micro-USB power connector
- Operating Temperature range of -10°C ~ 50°C
- Humidity < 80% (non-condensing)
- 95mm x 200mm x 70mm (W x D x H)
- Weight: 570g
- Accessories: WIFI Antenna, 18650 Lithium Ion battery x2



- DSP: Hisilicon Hi3518EV200
- Network: 4G
- System: Lite OS
- Sensor mode: AWB, AE, Automatic backlight compensation, Digital wide dynamic
- Solar charging, USB charging 6 hr full charge
- Active mode: 15s / 30s / 60s / always
- 4G connecting: Scan QR code
- Audio decode protocol: AAC & G.726
- Mic: -38dB high sensitivity
- Network: TCP/IP, HTTP, TCO, UDP, SMTP, DHCP, DNS, P2P
- Video: playback Time line and cloud storage
- IP 67
- APP: Ubell, ios10.0, android 5.0
- Status: indication blue & Red light





1080P Solar Wi-Fi Bullet Cam: SP-WF

Hardware Features

- 1/2.7" 1080P CMOS image sensor (PS5230)
- HD lens F2.8 FOV
- 90° Field of View
- Auto night vision mode
- H.264 video compression
- Siren aler
- Motion detection using smart PIR sensor
- 802.11 b/g/n Wi-Fi Protocol
- Two-Way audio, Support Full duplex intercom
- 850nm IR ray, 9m distance
- FHD resolution: 1920*1080/15fps, 640*360/30fps
- Micro SD slot supporting cards up to 64GB
- 2*18650 Li-battery, up to 60 days of standby time
- DC 5V Micro-USB power connector
- Operating Temperature range of -10°C ~ 50°C
- Humidity < 80% (non-condensing)
- 95mm x 200mm x 70mm (W x D x H)
- Weight: 560g
- Accessories: WIFI Antenna, 18650 Lithium Ion battery x2



- DSP: Hisilicon Hi3518EV200
- Wifi : Hisilicon Hi1131
- System: Lite OS
- Sensor mode: AWB, AE, Automatic backlight compensation, Digital wide dynamic
- Solar charging, USB charging 6 hr full charge
- Active mode: 15s / 30s / 60s / always
- Wifi configuration: air link + sound wave
- Audio decode protocol: AAC & G.726
- Mic: -38dB high sensitivity
- Network wifi: 2.4GHz
- Network: TCP/IP, HTTP, TCO, UDP, SMTP, DHCP, DNS, P2P
- Video: playback Time line and cloud storage
- IP 67
- APP: Ubell, ios10.0, android 5.0
- Status: indication blue & Red light



low power consumption

Dream of Smart Life

1080P Solar camera



Million HD cameras



WIFI network



Mobile phone viewing



Cloud-storage



Solar panel



TF storage



SP4G

4G^{LTE}

SPWF

Wi-Fi



Mobile phone
remote



Alarm
notification



Voice
intercom



Infrared night
vision



1080P HD



WIFI Connect



Multiplayer
online



TF storage

1080P Solar Cam

360 DAYS MONITORING

Supporting continuous rainy and rainy weather for about 60 days

0 electricity charges
Solar energy charging



Speech intercom audio monitoring

Outdoor rainproof and waterproof

TF card storage is convenient and safer

Memory Card Automatic Cyclic Coverage



pixel	1080P			
	Quality	Fluent	Standard	Clear High Definition
8G	50H	24H	18H	
16G	150H	48H	36H	
32G	200H	96H	72H	
64G	400H	192H	144H	

*The timetable is for reference only, depending on the physical environment.


1080P Solar Cam

Perfect fit for all kinds of site monitoring needs




SP4G-4G NO NEED FOR NETWORK / POWER

Solar wireless camera helps you solve all kinds of problems



1080P Solar Cam



MOBILE PHONE ALARM NOTIFICATION

When abnormal intrusion occurs in the surveillance area, the camera will push the alarm message to you. Mobile phones let you know the situation at home in time.



1080P Solar Cam

Remote monitoring of mobile phone Remote monitoring anytime, anywhere

You can watch scenes you care about happen anytime and anywhere on your mobile phone.

Everything, everything in the palm



THE STORAGE CONTENT OF THE CAMERA WILL BE AUTOMATI-

Voice intercom Real time call

Telephone anytime, anywhere, so that accompany more than one expression.



Clear speech



Noise reduction
optimization



Speech
enhancement



One key Talkback



WIFI connection high definition

Wireless CCTV Monitor NVR + 4 IPC



NVR-4C



FEATURES

4CH 1080P WIFI NVR FEATURES

- H.265 Compression System Option
- 4CH Realtime Recording, 1 CH Playback
- Motion Detection, Auto Cover Recording
- One Key Match for the System
- Max storage up to 6TB

HD WIFI CAMERA FEATURES

- H.264 Compression System Option
- 720P/960P/1080P WIFI IP Camera
- Array LEDS, 20M IR Distance
- One Key Match for the System
- PIR Light Function

Key Features:

- * 4MP Wireless Network Video Recorder
- * Built-in WIFI module with high-performance and high stability
- * Automatically Connection between NVR and IPC
- * Support video preview/recording/playback/backup
- * Support the mixed use of wireless and wire, support different scene
- * Support Android/IOS/PC remote

NVR-4C

Wireless CCTV Monitor

NVR Specialication

IP Video Input	4 CH x 720P/960P/1080P/3M/4M,RJ45 Interface
HDMI Output	1 CH, HDMI ;Resolution:1920x1080P/60Hz; 4K/30Hz
VGA Output	1CH (optional)
Video Compression	H.265, H.264
Recording /Playback	4*4M Recording,4*4M Playback 4*1080P Recording,4*1080P Playback
Video Resolution	720P, 960P, 1080P, 3M, 4M Recording
Frame Rate	15Fps
Stream Type	Audio/Video,Variable Rate(VBR) , Constant Bit Rate(CBR)
Audio Compression	G.711
Storage Type	1 * SATA Interface
Storage Capacity	6TB In Max
Backup	USB Backup
Network Interface	RJ45 10M / 100M Internet Interface
USB Interface	1 * USB2.0 Interface(Support Upgrade,Backup,Mouse)
Temperature	-10°----- 55°
Size	258mm×210mm×42mm
Operation System	Embedded Linux Operation System
Soft Power-Off	Not Support
Device Control	Remote Control & Mouse
Power Input	DC +12 V / 3.0A



WIFI Camera Specification

System Architecture	Cortex-A7 HI3516D
Image Sensor	1/3" Progressive Scan Sensor
S/N Ratio	> 39.1 dB
Resolution	2592 x 1520 16: 9 High Defination
Minimum Illumination	Color: 0.1 Lux B/W: 0.05 Lux
OSD	Date Time & Title
White Balance	Auto
Day&Night	IR cut filter with auto switch
3D-DNR	Auto
Mirror/Flip	On / Off
Privacy Masking	4 Zone Selectable
Video Codec	Two Streaming at the Same Time: H.264/H.265 2592x1520@15fps or below @128-12000Kbps H.264/H.265 720x576@15fps or below @128-1500Kbps
Audio Code	G.711 A-Law @ 16bits 8kbps
Thunder Prevention	Standard IEC61000-4-5
Connectors	RJ45 / WIFI 802.11b/g/n
1ch Analog audio in (optional)	
Power Input	DC12V
Power Consumption	≤6W
Operation Temperature/Humidity	-10℃ to +50℃ / 30% to 80% RH
Storage Temperature/Humidity	-20℃ to +60℃ / 20% to 90% RH



Remote Monitoring A Variety of Scense In the Master



Work with NVR, free mobile view Multiple cameras, monitoring different place.





Thank You !